



-86°C ULT Freezer MBI728-80



Energy saving

VIP(Vacuum Insulation Panel) design with extra insulation cuts down on heat loss to cabinet by 25% and helps reduce energy consumption by more than 20%, power consumption only 10.5 kWh/day



Slim design

Easily fits through every standard lab door and takes a small footprint



Reliable

Cabinet temperature can reach -86°C with temp uniformity within 5°C

Complementary products



CO₂
Backup
Systems



Chart
Recorder



Stainless
Steel
Racks



Cryo
Boxes

Specifications

MBI728-80

Technical Data

Type	-86°C ULT Freezer
Cabinet Type	Upright
Climate Class	N
Cooling Type	Direct cooling
Defrost Mode	Manual
Refrigerant	HC
Noise Lever (dB)	50

Performance

Cooling performance(°C)	-86
Temperature Range(°C)	-40~-86

Control

Controller	Microprocessor
Display	LED

Electrical Data

Power Supply(V/Hz)	115V/60HZ or 220V/60HZ
Power(W)	1000
Electrical Current(A)	10

Functions

High/Low Temperature	Y
Remote Alarm	Y
Hot Condenser	Y
Power Failure	Y
Sensor Error	Y
Low Battery	Y
High Ambient Temp	Y
Door Ajar	Y



Accessories

Caster	Y
Foot	Y
Test Hole	Y/2
Shelves/Inner Doors	3/4
Temperature Recorder	Optional
USB Interface	Y
Rs232/485 Interface	Optional
CO ₂ Backup System	Optional
LN ₂ Backup System	Optional
Racks & Boxes	Optional

Dimensions

Capacity(L/Cu.Ft)	728/25.7
Net/Gross Weight(approx)	345/385(kg) 760.6/848.8(lbs)
Interior Dimensions(W*D*H)	766*716*1310(mm) 30.2*28.2*51.6(in)
Exterior Dimensions(W*D*H)	1041*980*1980(mm) 41.0*38.6*78.0(in)
Packing Dimensions(W*D*H)	1090*1050*2150(mm) 42.9*41.3*84.6(in)
Container load (20/40/40'H)	12/20/20

Accessories & consumables

MBI728-80

Consumables

Racks		Part Code	
Model	DCJ-55-A		DCJ-55-B
Q'ty/Layer		5	
Dimension (W*D*H)	138*685*293(mm) 5.4*27.0*11.5(in)		140*685*293(mm) 5.5*27.0*11.5(in)

Boxes		Part Code		
Model	T130	HBB-200-PP	HBB-281-PC	HBB-200-C
Material	PP	PP	PC	PC
Dimension (W*D*H)	133*133*53.5(mm) 5.2*5.2*2.1(in)			
Q'ty/Rack		25		

Total Q'ty				
Racks		20		
Boxes		500		
Vials	40500	50000	40500	50000

CO₂ Backup System

Model	HBX-IC
Temperature range	-40°C to -70°C

LN₂ BackupSystem

Model	HBX- II A
Temperature range	-90°C to -135°C

Chart Recorder

Temperature range	+50°C to -115°C
-------------------	-----------------

Others

Certificate	CE
-------------	----

Complementary products



CO2
Backup
Systems



Stainless
Steel
Racks




Chart
Recorder



Cryo
Boxes